

# WBS MATERIAL SAFETY DATA SHEET

CREATION DATE: JUNE 26, 1990  
REVISION DATE: SEPTEMBER 24, 1998

DURO DYNE CANADA INC.  
5030 Francois-Cusson  
Lachine, Quebec H8T 1B3  
Phone: (514) 422-9760

Fax: (514) 636-0328, (888) DURODYNE

**Emergency Telephone Number: (781) 878-7015 (Business hours)**

**CANUTEC Emergency Telephone Number: (613) 996-6666**

<b>SECTION 01: WBS PRODUCT IDENTIFICATION</b>
---

TRADE NAME: DURO DYNE WBS DUCT SEALANT  
 PRODUCT CODE: 11-505 (WBS)  
 CAS NUMBER: Mixture  
 D.O.T. HAZARD CLASS: Not applicable  
 U.N. #: Not applicable  
 PROPER SHIPPING NAME: Non-Regulated  
 TECHNICAL NAME: Not applicable  
 HAZARD RATING ( none=0, extreme=4) HEALTH: 1, FIRE: 0, REACTIVITY: 0  
 PERSONAL PROTECTION: B (See Section 08)

MANUFACTURER:  
 TACC International Corporation  
 Air Station Industrial Park  
 Rockland, MA 02370  
 Emergency Telephone Number: (781) 878-7015  
 CANUTEC Emergency Telephone Number: (613) 996-6666

<b>SECTION 02: WBS HAZARDOUS INGREDIENTS</b>
--

Ingredient	CAS #	Weight %	Exposure Limits		VP	
			ACGIH/TLV	OSHA/PEL	mm	HG
Vinyl Acetate Monomer	108-05-4	<1.	10 ppm	10 ppm	0	
		STEL=	15 ppm	20 ppm		

### **SECTION 03: WBS PHYSICAL DATA**

BOILING RANGE: N/A  
EVAPORATION RATE: Slower than n-Butyl Acetate  
VOLATILES VOL %: 28.4  
WEIGHT %: 38  
APPEARANCE: Grey Colored Mastic  
VAPOR DENSITY: Heavier than air  
LIQUID DENSITY: Heavier than water  
WEIGHT PER GALLON: 10.86 lbs  
SPEC. GRAVITY: 1.30372

### **SECTION 04: WBS FIRE AND EXPLOSION HAZARD DANGER**

FLAMMABILITY CLASS: IIIB  
FLASH POINT: None  
UEL: N/A

EXTINGUISHING MEDIA: Foam; Dry chemical; Carbon dioxide; Water spray or fog.  
SPECIAL FIREFIGHTING PROCEDURES: Use cold spray to cool down fire / heat of exposed containers to keep them from rupturing.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers exposed to high heat may rupture due to pressure build-up.

### **SECTION 05: WBS HEALTH HAZARD DATA**

PERMISSIBLE EXPOSURE LEVEL: None

#### **EFFECTS OF OVEREXPOSURE:**

EYES: May be eye irritant.  
SKIN: Prolonged or repeated contact may cause irritation.  
INHALATION: None  
INGESTION: May cause gastrointestinal irritation.

#### **FIRST-AID:**

EYES: Flush with warm water for 15 minutes. If irritation or redness persists, seek immediate medical attention.  
SKIN: Remove contaminated clothing and cleanse thoroughly with soap and water. Seek medical attention if redness, blistering or swelling occur.  
INHALATION: Remove to fresh air.  
INGESTION: Drink two or three cups of milk or water. Seek medical advice.

### **SECTION 06: WBS REACTIVITY DATA**

STABILITY: Stable  
HAZARDOUS POLYMERIZATION: Will not occur.  
INCOMPATIBILITY: None known.  
CONDITIONS TO AVOID: Do not store above 125 Deg.F (52 Deg. C.) or below freezing or damage may occur to product.  
HAZARDOUS DECOMPOSITION PRODUCTS: None known.

**SECTION 07: WBS SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Confine to small area. Use absorbent to clean up. Place in container for disposal.

WASTE DISPOSAL METHOD: Dispose in accordance with federal, state and local regulations.

**SECTION 08: WBS SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION: If vapors exceed TLV use self contained organic mask NIOSH approved.

VENTILATION: Sufficient to keep workroom concentration below TLV.

PROTECTIVE GLOVES: Chemical resistant gloves.

EYE PROTECTION: Safety glasses or face shield.

OTHER PROTECTIVE EQUIPMENT: Barrier cream for sensitive skin.

**SECTION 09: WBS SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store above 125 Deg.F (52 Deg. C.) or below freezing or damage may occur to product.

OTHER PRECAUTIONS: None

**SECTION 10: WBS ADDITIONAL REGULATORY INFORMATION**

SARA TITLE III SECTION 313

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Cas #	Chemical Name	Percent by Weight
108-05-4	Vinyl Acetate Monomer	< 1.

PROP 65 (CARCINOGEN)

WARNING: This product contains a chemical known to the state of California to cause cancer.

CAS #	Chemical Name
14808-60-7	Crystalline Quartz
14808-60-7	Silica, Quartz

PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

PROP 65 (BOTH CARCINOGEN AND TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause cancer or birth defects or other reproductive harm.

## **WBS ADDITIONAL INFORMATION:**

**\*\* The information given and the recommendations made herein apply to our product(s) alone and are not combined with other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No Guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes. \*\***

## **WBS TECHNICAL CONTACT**

FOR INFORMATION CONTACT:

M.S.D.S. Co-Ordinator

**Duro Dyne Canada Inc**

(514) 422-9760