



Duro Dyne Canada Inc

***VOC/LEED Sealer & Adhesive Summary**

Product Code	DWN	WB-S2	WSA	WIT	S-2	IA-94	RPG
VOC grams/litre (less water)	28 g/l	48 g/l	<5 g/l	<5 g/l	539 g/l	528 g/l	536 g/l
Solids %	69%	69%	57%	55%	45%	33%	30%
Weight-lb./gl.	11.7 lbs/US gl.	11.7 lbs/US gl.	11.8 lbs/imp. gl	11.8 lbs/imp. gl	8.9 lbs/US gl.	6.3 lbs/US gl.	4.4 lbs/US gl.

VOC information on GU & GN Gasketing products:

VOC: Since VOC ratings apply to wet adhesives that evaporate as part of the application process, the solvent is removed from the adhesive on the gasket when fabricated. The GN/GU gasket is thus a dry product for which VOC are not required.

MSDS: Duro Dyne is complying fully with the Federal Occupational Safety and Health Administration (OSHA) standard 29 C.F.R. 1910.1200. The GN does not require an MSDS because it is considered an "Article" and articles are exempt from the MSDS provisions.

*VOC: Volatile Organic Compounds

LEED: Leadership in Energy and Environmental Design

August 12, 2013