



DURO DYNE CANADA INC. 2365 46<sup>e</sup> AVENUE, LACHINE, QUEBEC H8T 3C9  
TEL : (514) 422-9760 FAX : (514) 636-0328  
[www.durodynecanada.ca](http://www.durodynecanada.ca)

### \*VOC/LEED Sealer & Adhesive Summary

Product Code	DWN	WSA	WIT	RPG
VOC grams/litre (less water)	28 g/l	<5 g/l	<5 g/l	536 g/l
Solids %	69%	57%	55%	30%
Weight-lb./gl.	11.7 lbs/US gl.	11.8 lbs/imp. gl	11.8 lbs/imp. gl	6.4 lbs/US gl.

#### VOC information on GU & GN Gasketing products:

**VOC:** Since VOC ratings apply to wet adhesives that evaporate as part of the application process, the solvent is removed from the adhesive on the gasket when fabricated. The GN/GU gasket is thus a dry product for which VOC are not required.

**SDS:** Duro Dyne is complying fully with the **Federal Occupational Safety and Health Administration** (OSHA) standard 29 C.F.R. 1910.1200. The GN does not require an MSDS because it is considered an "Article" and articles are exempt from the MSDS provisions.

\***VOC:** Volatile Organic Compounds

**LEED:** Leadership in Energy and Environmental Design