



Suspension systems typically use threaded rod with washers and nuts to construct a support structure. Sizing, cutting and assembling the rods to the complementary parts and fastening them to an anchor point can be very time consuming.

The Zip-Clip cable lock combined with wire rope is a more efficient method. The Zip-Clip has a spring loaded pawl which allows entry and passage of wire rope through the cable lock. Once engaged by the pawl, the wire rope is gripped with increasing pressure as the suspended load is increased. To ease adjustment, each Zip-Clip cable lock has an integrated release to disengage the gripping pawl.



"T" shaped release



Zip-Clips are suitable for use with single or multi-tiered trapeze systems and in applications supporting such items as rectangular ductwork, cable trays, baskets, etc.

- A work load limit of 220 lbs (100 kg)
- Sold in sets with looped cable
- Built in 5:1 safety factor
- Fits inside strut

Ordering Information			
Item #	Code	Description	Quantity
30041	ZCWR05	Zip-Clip Cable Lock and Looped Cable - 5 ft	10 bags of 10 sets
30042	ZCWR10	Zip-Clip Cable Lock and Looped Cable - 10 ft	10 bags of 10 sets
30043	ZCWR15	Zip-Clip Cable Lock and Looped Cable - 15 ft	10 bags of 10 sets
30044	ZCWR25	Zip-Clip Cable Lock and Looped Cable - 25 ft	10 bags of 5 sets
30104	DZCWR5	Double Zip-Clip Cable Lock and Looped Cable - 5 ft	10 bags of 10 sets
30105	DZCWR10	Double Zip-Clip Cable Lock and Looped Cable - 10 ft	10 bags of 10 sets
30106	DZCWR15	Double Zip-Clip Cable Lock and Looped Cable - 15 ft	10 bags of 10 sets
30107	DZCWR25	Double Zip-Clip Cable Lock and Looped Cable - 25 ft	10 bags of 5 sets

**To insure the safety and integrity of the Zip-Clip suspension system use only Duro Dyne wire rope supplied in the set.**



**Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346**  
**Duro Dyne Midwest Division, Fairfield, OH 513-870-6000 Fax: 513-870-6005**  
**Duro Dyne West Division, Fontana, CA 562-926-1774 Fax: 562-926-5778**  
**Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328**  
[www.durodyne.com](http://www.durodyne.com) E-mail: [durodyne@durodyne.com](mailto:durodyne@durodyne.com)

