



Tool Division

Reciprocating Saw Blades

- Duro Dyne Reciprocating Saw Blades fit all reciprocating saws using 1/2" universal shank.
- Saw Blades are bi-metal construction for long life and rugged use. This alloy steel features excellent flexibility.
- The teeth are hardened giving the blades a high speed cutting edge, long life and durability.
- Duro Dyne Reciprocating Saw Blades from Duro Dyne are thicker than most blades. This helps them stay sharper longer. Also, a thicker blade resists overheating and embrittlement.



Ordering Information

Item #	Code	Length	TPI	Qty Per Pkg.	Recommended Use
818155	DD075	6"	10	5	GENERAL PURPOSE - Wood with nails, Metal & non-ferrous metal and pipes with wall thickness over 3/8"
818169	DD088	6"	6	2	PLASTER & DRYWALL
818159	DD065	6"	6	5	WOOD WITH NAILS - Roughing, Fast work, Nail embedded knotty wood Remodeling
818164	DD066	9"	6	5	
818166	DD067	12"	6	5	
818165	DD086	8"	10/14	2	HEAVY DUTY - Long life blade for cutting pipe, structural and stainless steel from 1/8 to 1/2 in. thick. Fire and rescue work.
818156	DD059	6"	14	5	METAL CUTTING - Pipe, structural and stainless steel 3/32 - 1/4 in.; non-ferrous metal 3/32 - 3/8 in.
818157	DD057	6"	18	5	METAL CUTTING - Sheet metal and pipes with wall thickness from 1/8 to 3/16 in.
818163	DD060	8"	18	5	
818158	DD058	6"	24	5	METAL CUTTING - Sheet metal and pipes with wall thickness up to 1/8 in.

Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346
 Duro Dyne Midwest Division, Fairfield, OH 513-870-6000 Fax: 513-870-6005
 Duro Dyne West Division, Santa Fe Springs, CA 562-926-1774 Fax: 562-926-5778
 Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328
 www.durodyne.com E-mail: durodyne@durodyne.com



© Duro Dyne Corp.
 Printed in USA 8/06
 BG818404