


SUBMITTAL RECORD _____
 JOB _____
 LOCATION _____
 SUBMITTED TO _____
 SUBMITTAL PREPARED BY _____
 APPROVED BY _____
 DATE _____



Submittal Form Duro-Gum™

DESCRIPTION

Duro-Gum is a gray, permanently soft, non-toxic compound which will adhere to most clean dry surfaces. It has countless applications in the refrigeration, heating and cooling, plumbing, and metal fabrication fields. It will seal around electrical boxes, flashings, and service mast entries. Duro-Gum can be shaped by hand to any form and reused if necessary. It is an excellent general purpose sealant.



FLAME SPREAD: 5
 SMOKE DEVELOPED: 15

FEATURES

- Meets UL 723
- FDA Approved
- U.S.D.A. Acceptable
- Dielectric Strength: Approx. 200 volts per mil (ASTM D149-64) or 10 KV
- Chemical Resistance: Excellent resistance to water, alcohols, mild acids and bases
- Vehicle Bleedout: None
- Non-Corrosive: Will not corrode Metals
- Non-Irritant: No irritation to eyes or skin as listed in CFR, Title 16, "Appraisal of the safety of chemicals in food, drugs, and cosmetics"
- Paintable

TYPICAL PROPERTIES

Color: Gray
Base: Non-drying synthetic polymers and oils
Temp. usage range: 25°F to +120° F
Temp. tolerance range: -30°F to +175° F
Specific Gravity: 1.65 to 1.7
Cone penetration: Load of 300 gm..5 sec. @ 25°F;
 100 -115 mm/10

Item #	Code	Description
21048	BTLG1	Duro-Gum

