

SUBMITTAL RECORD _____
 JOB _____
 LOCATION _____
 SUBMITTED TO _____
 SUBMITTAL PREPARED BY _____
 APPROVED BY _____
 DATE _____



Submittal Form

Duro-Line™



DESCRIPTION

Duro-Line was designed and developed to MIMIC cooper, creating the perfect replacement for copper line sets. Duro-Line's patented technology creates the perfect balance of strength and flexibility, coupled with superior roundness that holds its shape, even when cut. The Low Carbon Steel Line Set has built-in corrosion and chemical resistance that is unmatched in the inudstry. This time-tested technology is why Duro-Line is the better line set.

FEATURES & BENEFITS

- Trusted Duro Dyne quality
- 20-year warranty on the tubing; 5-year warranty on the insulation
- Built-In Corrosion Resistance - Engineered to withstand the elements and extend service life. Tested for 40 years
- UV Insulated and Uninsulated in a variety of lengths
- Carries all known HVAC & Refrigeration refrigerants
- Handles extreme temps: -55° F to 500° F (A2L and A3 approved)
- Significantly less volatile commodity than copper
- Outperforms copper in corrosion resistance and pressure capacity
- Lighter weight than copper makes for quick and easy installation

Code	Description	Liquid Line	Suction Line	Insulation		Length
SLS1451625	1/4 LL, 5/16 SL X 25' W/Insulation	1/4"	5/16"	1/2"	Both Lines	25'
SLS1451650	1/4 LL, 5/16 SL X 50' W/Insulation	1/4"	5/16"	1/2"	Both Lines	50'
SLS143815	1/4 LL, 3/8 SL X 15' W/Insulation	1/4"	3/8"	1/2"	Both Lines	15'
SLS143825	1/4 LL, 3/8 SL X 25' W/Insulation	1/4"	3/8"	1/2"	Both Lines	25'
SLS143850	1/4 LL, 3/8 SL X 50' W/Insulation	1/4"	3/8"	1/2"	Both Lines	50'
SLS141215	1/4 LL, 1/2 SL X 15' W/Insulation	1/4"	1/2"	1/2"	Both Lines	15'
SLS141225	1/4 LL, 1/2 SL X 25' W/Insulation	1/4"	1/2"	1/2"	Both Lines	25'
SLS141250	1/4 LL, 1/2 SL X 50' W/Insulation	1/4"	1/2"	1/2"	Both Lines	50'
SLS5165830	5/16 LL, 5/8 SL X 30' W/Insulation	5/16"	5/8"	1/2"	Suction Line	30'
SLS5165850	5/16 LL, 5/8 SL X 50' W/Insulation	5/16"	5/8"	1/2"	Suction Line	50'
SLS5163725	5/16 LL, 3/4 SL X 25' W/Insulation	5/16"	3/4"	1/2"	Suction Line	25'
SLS5163430	5/16 LL, 3/4 SL X 30' W/Insulation	5/16"	3/4"	1/2"	Suction Line	30'
SLS5163450	5/16 LL, 3/4 SL X 50' W/Insulation	5/16"	3/4"	1/2"	Suction Line	50'
SLS5167825	5/16 LL, 7/8 SL X 25' W/Insulation	5/16"	7/8"	1/2"	Suction Line	25'
SLS5167830	5/16 LL, 7/8 SL X 30' W/Insulation	5/16"	7/8"	1/2"	Suction Line	30'
SLS5167850	5/16 LL, 7/8 SL X 50' W/Insulation	5/16"	7/8"	1/2"	Suction Line	50'

CONTINUED ON REVERSE SIDE

SUBMITTAL RECORD _____
 JOB _____
 LOCATION _____
 SUBMITTED TO _____
 SUBMITTAL PREPARED BY _____
 APPROVED BY _____
 DATE _____



Submittal Form

Duro-Line™



CONTINUED FROM REVERSE SIDE

Code	Description	Liquid Line	Suction Line	Insulation		Length
SLS385825	3/8 LL, 5/8 SL X 25' W/Insulation	3/8"	5/8"	1/2"	Suction Line	25'
SLS385835	3/8 LL, 5/8 SL X 35' W/Insulation	3/8"	5/8"	1/2"	Suction Line	35'
SLS385850	3/8 LL, 5/8 SL X 50' W/Insulation	3/8"	5/8"	1/2"	Suction Line	50'
SLS383425	3/8 LL, 3/4 SL X 25' W/Insulation	3/8"	3/4"	1/2"	Suction Line	25'
SLS383435	3/8 LL, 3/4 SL X 35' W/Insulation	3/8"	3/4"	1/2"	Suction Line	35'
SLS383450	3/8 LL, 3/4 SL X 50' W/Insulation	3/8"	3/4"	1/2"	Suction Line	50'
SLS387825	3/8 LL, 7/8 SL X 25' W/Insulation	3/8"	7/8"	1/2"	Suction Line	25'
SLS387835	3/8 LL, 7/8 SL X 35' W/Insulation	3/8"	7/8"	1/2"	Suction Line	35'
SLS387850	3/8 LL, 7/8 SL X 50' W/Insulation	3/8"	7/8"	1/2"	Suction Line	50'
SLS1450U	1/4 Uninsulated Line Set 50'	1/4"		None		50'
SLS51650U	5/16 Uninsulated Line Set 50'	5/16"		None		50'
SLS3850U	3/8 Uninsulated Line Set 50'	3/8"		None		50'
SLS1250U	1/2 Uninsulated Line Set 50'	1/2"		None		50'
SLS5850U	5/8 Uninsulated Line Set 50'	5/8"		None		50'
SLS3450U	3/4 Uninsulated Line Set 50'	3/4"		None		50'
SLS7850U	7/8 Uninsulated Line Set 50'	7/8"		None		50'

Duro Dyne Corporate Headquarters, Bay Shore, NY

631-249-9000 • Fax: 631-249-8346

Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada

www.durodyne.com • E-mail: durodyne@durodyne.com



8/7/2025